MANDARI DEGREE COLLEGE, MANDARI, DIST-BHADRAK

Notice No. 026

Date. 23/05/2025

TENDER CALL NOTICE

Sealed quotations are invited from the reputed manufacturer, their Authorized Dealer/Sole Selling Agents/ Stockiest/ Servicing Agencies/Firm for supply & installation of IT equipments at Mandari Degree College, Mandari of Bhadrak District. The details regarding the tender (Brand, Brief Specification etc.) may be downloaded from the District website of Bhadrak and College website of i.e. www.bhadrak.nic.in & www.mandaridegreecollege.org.in respectively. Henceforth the Tender complete in all respect should be submitted to Principal, Mandari Degree College, Mandari, Dist-Bhadrak. The quotation should reach this office through Registered Post/Speed Post/Courier latest by 06.06.2025.

Principal, Mandari Degree College, Mandari.

INVITED FOR BIDS

BID DOCUMENT FOR PURCHASE OF DESKTOP COMPUTERS, MFD/MFPs, & ITS PERIPHERALS OF MANDARI DEGREE COLLEGE, MANDARI, BHADRAK DISTRICT.

1.	Terms & Conditions		Annexure-A
2.	Tender Application Format/Details of Bidder	iā.	Annexure-B
3.	List of Items(Specification details)		Annexure-C

TERMS & CONDITIONS.

- 1 The intending bidders may apply for in our prescribed Performa/ format by downloading bid form and documents from the website www.bhadrak.nic.in
- 2 The quotationer shall furnish the true copy of the authorized dealer certificates issued from the company brand.
- The interested firms are advised to submit the envelope containing the quotation/ tender should be properly sealed (preferably wax/ cello tape seal) and super scribed as "Sealed tender against Tender Call Notice No______ Dated ______ for "SUPPLY & INSTALLATION OF _____ IT EQUIPMENTS _____ "to the Principal, Mandari Degree College, Bhadrak, At- Mandari, PO- Mandari, Pin- 756125, Dist-Bhadrak, Odisha. If the envelope containing the quotation is not sealed and marked as above, the undersigned will assume no responsibility for its misplacement or premature opening.
- 4 The number and quantity mentioned in the above Tender Notice is the probable number and quantity required to be purchased. The same may be increased or decreased according to the requirement.
- 5 The sealed documents shall be opened at the Principipal Office, Mandari Degree College, Mandari, Bhadrak on 10.06.2025 at 10.30 A.M. in presence of bidder or their authorized representatives and the District Technical/Purchase Committee. In case of any unavoidable circumstances, if the Tender could not be opened on the scheduled date, then the rescheduled date will be fixed & notified as per decision of the authority.
- 6 Only Registered post/Speed post/currier quotation will be allowed and the authority shall not be responsible for any type of postal delay. Conditional/Incomplete quotations are liable for rejection.
- 7 The intending bidder should submit an affidavit that his/her firm has not been black listed by any Govt. organization.
 - 8 Model/Specification and Price should be clearly maintained by the bidder in the rate quoted format.
 - 9 The Specification/configuration mentioned in Annexure-C may be same or higher. If the vender/bidder will apply in lower specification of the tender, those vendors will be summarily rejected.
 - 10 Please enclose your valid up-to-date GSTIN No., PAN Card No. and ITR/TDS clearance certificate. If selected, then the supplier has to submit every document needed by this office for payment.
 - 11 The bidder must submit guarantee and warranty for minimum period 3 years of Desktop Computer, MFD/MFPs 3 years and 2 years of Battery for 600VA offline UPSs.
- 12 The Bidders/Vendors are requested to highlight/underline the specifications in the Technical Brochure as per the specification. The company should submit all relevant drawings & sketches of each product separately in line with specifications along with the bid.

- 13 Quoted price should include cost of items/equipments/services, installation commissioning, transportation to designated location, maintenance cost for OEM warranty periods and taxes/duties etc.
- 14 The Authority reserves the right to negotiate with the successful bidders only.
- 15 Any difference or variations in the brand name or specification other than our specification should not be entertained.
- 16 Tender(s) without appropriate EMD will be rejected at the spot of opening of the tender and no reconsideration will be made.
- 17 Arithmetical errors in the financial bids will be rectified on the following basis. If there is a discrepancy between the unit price and the total price that is obtained by multiplying the unit price and quantity, the unit price shall prevail and the total price shall be corrected. If the supplier does not accept the correction of errors, it's bid will be rejected. If there is a discrepancy between the price quoted in words and figures, the rate quoted in words will be taken as final and shall be binding on the agency.
- 18 The date of delivery mentioned in order should be strictly adhered, the office reserves the right not to accept the delivery in part or full and to claim the liquidated damages/Penalty at 1% per week or part thereof subject to a maximum of 10% of the total value of the supply order which may be deducted from the final bill.
- 19 The rate quoted for items should be inclusive of all taxes, installation charges and transportation charges.
- 20 The EMD(refundable) Rs.5000/-,Tender paper cost (Non-refundable) is Rs. 500/- shall be deposited in shape of Bank Draft drawn on any Nationalised Bank in favour of Principal, Mandari Degree College, Mandari, Bhadrak payable at Bhadrak.
 - 21 EMD will be forfeited if the vendor fails the terms and condition.
 - 22 Payment will be released after submission of delivery certificate, PDI, Installation Certificate, Stock entry Certificate.
 - 23 In event of any dispute, the matter shall be finalised/settled within the jurisdiction of the Bhadrak.

Place:		
Date:		Seal & Full Signature of the Applicant

CHECK LIST

SL NO	Description	Start page	End page	Total page
01	TENDER COST INSHAP OF BANK DRAFT.			
02	SELF ATTESTED COPY OF GST REGISTRATION CERTIFICATE.			
03	SELF ATTESTED COPY OF PAN CARD			
04	SELF ATTESTED COPY OF LAST INCOME TAX RETURN			
05	SELF ATTESTED COPY OF AUTHORIZATION CERTIFICATE			
06	SELF ATTESTED COPY OF BIDDER'S PROFILE			
07	COPY OF BROCHURE IN SUPPORT OF TECHNICAL SPECIFICATION OF EQUIPMENT			
08	SELF-DICLARATION FOR NON- BLACKLISTING COPY			
09	PRICE SCHEDULE			
10	EXPERIENCE OF EXECUTION OF SIMILAR WORK.			

Annexure-C

HP 280 G9 DESKTOP SPECIFICATIONS

SL NO	MAKE/MODEL	ITEMS	SPECIFICATIONS	UNIT	PRICE		
1	HP 280 G9	CABINET FORM	TOWER /MICRO TOWER 15.1 to 26	01			
	commercial desktop	FACTOR	ltr	01			
	commercial desktop	Mother board Chipset	Intel H670 ·				
		number	mici riovo				
		Processor make	INTEL				
		PROCESSOR	X86/64 BIT architecture				
		processor generation	Core i3 13th				
		Processor description	Intel Core i3				
		Processor number	Intel core i3 13100				
		Number of core &	Max turbo frequency 4.5 Ghz				
		threads per processor	4 cores and 8 threads				
		Operating system	Microsoft win 11 home factory preloaded				
		Ram size	DDR4 8GB 3200 (16*1) 2 DIIM slots				
		Ram expandability	64 GB				
		Integrated graphics	Intel UHD graphics 770				
		Supported for discrete	yes				
		NVIDIA/AMD graphics	, , , ,				
		card up to 6 GB					
		Type of drives used	NVMe SSD				
		Total SSD Capacity	512 GB NVMe SSD				
		Optical drive	NA				
		Hdd	NA				
		Drive bays	two				
	¥ .	Slots for up gradation	1 pci express 4.0/1 pci express3.0/1 pci slots for WLAN & St		ght)/2 M.2		
		LAN	LAN integrated 10/100/1	000 M			
		PORT &	Front 1 headphone/microphone combo,:		need USB		
		CONNECTORS	GBPS signaling rate.2 super speed USB 10 GBPS signaling rate,1 USB TYPE C, total 6 no's USB in front for easy accerear, 1 HDMI,1 SERIAL,1 Line in,1 line out,1 power connector,1 rj-45,1 dp,2 USB 2.0				
		Firmware trusted platform Module	Tem 2.0				
		Hardware security lock slot	yes				
		Power supply	180-260 watt internal power supply with minimum 90% efficiency				
		Certificate	OOEM authorization				
		Keyboard and mouse	USB keyboard and USB	mouse			
		HP Monitor	19.5" LED display CTO & OEN		TED		
		YEARS OF WARRENTY	3 YEAR ONSITE WARE	RENTY			

APC 600 VA UPS

		Section 201	600 VA UPS			
SL.NO	MAKE/MODEL	ITEMS	SPECIFICATIONS	UNIT	PRICE	
01	APC/600VA	UPS CAPACITY	600 VA	01		
		Input voltage	230 v AC			
		Grownout transfer	145 v AC .			
		Over voltage	230 v AC			
		Voltage on battery	230 v AC			
		Frequency on battery	50 Hz			
		Transfer time	50 hz 6 ms			
		Air Ventilation	Side & back			
		Protection from	UPS have conformal paint coating on pcs for insulation for dust and humidity UPS have battery saver option to increase the			
		Humidity and dust				
		Battery saver option				
		No load shutdown	UPS WORK on load of 2 to 3 watts also			
			Full time 160 votes			
		Ac surge protection Automatic Re start of	YES			
	54	UPS	YES			
		TYPE maintenance free	12v,7.2 AH			
		Typical recharge time	4-6 hours			
		Operating temperature	0 c to 45 degree c			
		Strong temperature	-15 c to 45 degree c			
		3 power outlets	With battery backup	and surge prot	ection	
		Power cord	1.2 meters	0 1		
		Runtime for single pc load	30 min normal mode			
		Runtime for	15 min normal mode			
	_	workstation pc load				
		Battery saver	Toggle button			
		Certification	BIS			
		Designed and manufactured in India	yes			
		WARRENTY	2 YEARS			
		A STATE OF THE STA				

LASERJET PRINTER

SL	MAKE	ITEMS	SPECIFICATIONS	QT	PRICE
NO	/MOD EL		SILONIONS	Y	ridel
1	HP		M3104 FDW LASERJET ALL-	01	
			IN-ONE PRINTER	(1)	
		Core Function	Print, Scan and Copy		
		Original document feeder type	Automatic Document Feeders		
		Print Technology	Laser		
		Cartridge Technology	Composite Carlridge		
		Type of Printing	Monochrome (Black)		
		RAM Size (MB	256		
		Features	fax		
	Operation	g System Compatibility	Windows '10 and Above,Linux,MacOS,	Windows	Serve
	Operatin	Feeder capacity	31 to 40		
		Number of main paper tray	1		
		Print Paper Size	A4 and Legal		
		Minimum Print Speed per Minule	26 to 30		
		Auto Duplexing Prinling/Coping (2-sided Feature)	yes		-
	6	Maximum Scan Area (Platen/Flatbed Size)	44 and Legal		
		44 Scan Speed -Colour (Image Per Minute) @ 300 x 300 dpi	'11 lo 20		
		A4 Scan Speed - Mono (Image Per Minute) @ 300 x 300 dp	Email -11to20		**
		COPYING Reduction and Enlargement	yes		
		Total paper tray combined capacity	200		
		Bypass paper tray	NO		
		Connective	USB Port/Ethernet PORT/wife		
		Minimum yield of the cartridge ink tonner supplied with machine as per	700		
		Minimum duty cycle	20,000		
		Power supply	Single phase AC 220-240 V		
		Maximum power consumption	1300		
		Minimum operating temperature	10 degree		
		Minimum operating temperature	30		

Television

SL	MAKE	ITEMS	SPECIFICATIONS	QTY	PRICE
NO	/MOD EL	TILIVIS	SELECTIONS	QII	TRICE
1	SONY	Screen size	65" inch	01	
1	50,11	Brightness	350 nits		
		Contrast ratio	1200		
		Dynamic contrast ratio	400.000		
		Response time	8.0		
		Display resolution	3840 * 2160		
		HDR compatibility	yes		
		Aspect ratio	16;9		
_		Portrait / tilt compatibility	yes	_	
		Dimming type	Frame dimming		
		Display device	LCD		
		PANEL TYPE	IPS		
		BACKLIGHT TYPE	Direct LED		
		COLOR GAMUT	69%		
		OPERATION TIME	16/7	_	
		HAZE	1%		
		VIEWING ANGLE R/L	178 DEGREE		
		VIEWING ANGLE UP/DOWN	178 DEGREE		
		HDMI SIGNAL	4096*2160P		
	-	SPEAKER POSITION	DOWN FIRING		
		Audio power output	10w+10w		
		Pro settings	yes		
		HDMI auto wake-up	yes		
		Operating system	Android TV		
		On board storage	16 GB	_	
		RAM	3 GB		
		WI-FI Certified	yes		
		Wireless LAN	integrated		
		USB Playback codec	MPEG1	_	
		On screen clock	yes		
		Sleep timer	yes		
		On/off timer	yes		
		Chromecast built-in	yes		
	-	Apple airplay	yes		<u> </u>
		Ip control	yes		
		RS-232C CONTROL	YES		
		HDMI CEC	YES		
		HDCP	HDCP 2 FOR HDMI 1 2 3		
	-	COMPPOSITE VIDEO INPUT	1 SIDE		-
		Minimum operating humidity	20		
		Maximum operating humidity	80		
		Standard machine weight	11 kg		

Wire less Mice & Camera with MIC for Virtual meeting

SL NO	MAKE	ITEMS	SPECIFICATIONS	UNIT	PRICE
	Logitech	BCC 950	Logitech Master Series Graphite MX Brio 4K Ultra Hd Web Camera, 960- 001548	01	
		Connectivity	USB-C to USB-C Cable		
		Focus Type	Advanced Autofocus		
		Package Contains	MX Brio, Mount Clip with Removable Adapter, USB-C to C 3.0 Cable, User Documentation		
		Microphone Type	Dual Beamforming		
		Width	98 mm		
		Zoom	4x Digital Zoom		
		Type of Product	Web Camera		
		Part No	MXBRIO4KGRPT		
		Height	44 mm		
_		Weight	137 g		
		Lens Type	Glass		
		Interface	USB 3.0		
		Color	Graphite		
	-	Resolution	4K/30 fps, 1080p/60 fps		
_		Image Sensor	8.5 MP Sony STARVIS		
		Model No	960-001548		
		Suitable For	Laptops, LCD Displays, or Monitors		
		Name of Manufacturer/Packer/Importer	Logitech International		
		View	90°/78°/65°		
		Mic Range	Up to 1.2 m		
		Depth	36 mm		
		Series	Master Series		

INTERNET AND NETWORKING

SL NO	MAKE	ITEMS	SPECIFICATIONS	UNIT	PRICE
1	D- LINK	CAT 6	CAT6 UTP 23AWG Solid:305M	/MTR	
		Category	6 UTP Solid cable		
		Conductor Meta	Bare Copper		
		OD	6.1mm ±0.2		
		Capacitance Unbalance	330pF/100m		
		Conductor	23 AWG (Solid)		
		Insulation Material	HD-PE		
		Resistance Unbalance	5% Max		
		Delay Skew	<45nS		

Pairs are braided in aluminum foil with drain wire/4-pair unshielded twisted pair (UTP) cable/Comply with Cat6 specifications/23 AWG solid copper conductor for superior conductivity/FR PVC Jacket/UL-listed/Verified compliant with EIA/TIA standards by ETL

RJ45 CONNECTOR

SL NO	MAKE	ITEMS	SPECIFICATIONS	UNIT	PRICE
1	D- LINK	RJ45 CONNECTOR	RJ45 CONNECTOR	01	
		connector/Use for 24-26 modular plug supports connectors of 100pcs/P transparent color/Coppe plating/Operating temper 26 AWG stranded v	rts 4 twisted pairs/8P8C type of 6 AWG stranded wires/RJ45 4 twisted pairs, 8 positions, 8 Pack/Housing: PC, UL94V-2, r Alloy/03MU micro-inch gold rature:-40°C to 80°C/Use for 24-wires, meet wiring scheme 8A/T568B		

16 PORT SWITCH SL NO MAKE ITEMS UNIT PRICE **SPECIFICATIONS D-LINK 16 PORT GIGA** D-LINK D-LINK 16 PORT GIGA SWITCH 01 Alarm Port No Humidity Operating: 10% ~ 90% RH Storage: 5% ~ 90% RH Interfaces 16 x 1000Base-TX Auto MDI/MDIX **Maximum Forwarding Rate** 2.38 Mpps **Max Power Consumption** 2.69 W **Packet Buffer Size** 2 MB Power Input 100 to 240 V AC **Switching Capacity** 3.2 Gbps **Temperature** Operating: 0 ~ 40 °C Storage: - 40 ~ 70 °C 0.27 kg Weight